

AUTOMATIC FILLING MACHINE DF 32 A

The allrounder for the sausage kitchen

On account of it's compact, robust and highly efficient method of construction, the automatic filling machine DF 32 A is an ideal device for filling, portioning and twisting of all kinds of sausages. With a portioning speed of up to 200 portions/minute and a portioning range of 5g to 10.000g (adjustable in 0,1g steps) the machine is ideal for medium sized butcher's shops, and for shift working supermarkets.

Even so the DF 32 A is a mobile machine, it's high dead-weight guarantees a good stability. The user-friendly touchscreen allows to easily make all the adjustments in weight, number of portions, number of twists and the time between the portions.

The closed oil system and it's stainless-steel oil tank prevent detergent and condensation water from interrupting the oil circulation. This way, maintenance is needed to a low degree and the service life of both the hydraulic pump and the valves is increased. Since the piston rod is made of stainless-steel, a high service life of the hydraulic cylinders is guaranteed as well.





AUTOMATIC FILLING MACHINE DF 32 A

DETAILS









Machine type

- Completely stainless-steel
- Cylinder volume: 32 Ltrs.
- Stainless-steel cylinder
- Polyethylene piston
- Machine for filling, portioning, twisting of kinds of sausages
- Portioning speeds: up to 200 portions/minute
- Portioning range: 5g 10.000g, adjustable in 0,1g steps

- Programmable are:
 - -Weight of the portions
 - -Number of portions
 - -Number of twists
 - -Time between portions
- User-friendly touchscreen
- Protection cover for touchscreen
- Mobile edition

Drive

- Maintenance-free electric engine with hydraulic pump
- 2,6 kW / 400 V / 50 Hz
- CEE jack 16 A

Hydraulics

- Closed hydraulic system
- Stainless-steel oil tank, separately integrated in cabinet
- Pump pressure: 130 bar

Specifications

	DF 32 A
Cyliner volume (I)	32
Power (kW)	2,6
Pump pressure (bar)	160
Max portions/minute	200
No. of twists	0 - 10
Voltage (V)	400
Control voltage (V)	24
Safety fuse (A)	16 (träge)
Dimensions (mm)	
Width	700
Depth	745
Height	1570
Weight (kg)	380
Accessories	Tool to dismantle pistons 3 filling pipes (14, 20, 30 mm)

DMS Maschinensysteme