

## **CUTTER DMK 120 V2AW**

#### **Professional Design**

The DMK 120 V2 AW cutter is the ideal cutter for larger meat processing plants due to its robust design. The well thought-out design offers the user almost unrestricted use in all areas of application. The machine is equipped with two independently operable, powerful motors that offer a high degree of control versatility.



The cutter impresses with its extremely quiet, low-vibration operation, even in the high speed range.

The elaborate manufacturing of the individual components is carefully and precisely coordinated. The thick-walled cutter bowl, cast from high-quality stainless steel, has an extremely precise concentricity, which allows the cutter knives to be set tightly in the bowl radius. The bearing technology of the cutter bowl allows durable use even at high speed.

# **CUTTER DMK 120 V2AW**

### **DETAILS**





### **Specifications**

opecifications					
	DMK 45 C2	DMK 45 V2	DMK 80 C2/C2AW	DMK 80 V2/V2AW	DMK 120 V2AW
Bowl volume (litres)	45	45	80	80	120
Capacity (ca. kg)	32	32	64	64	96
Number of blades	6	6	6	6	6
Revolution (rpm)	1500 / 3000	1000 – 3600	1500 / 3000	1000 – 3600	1000 – 4000
Variable revolution (rpm)	-	150 – 300	-	150 – 300	150 – 300
Power of blade shaft (kW)	8,0 / 9,5	11	18,0 / 21,0	23	30
Voltage	400	400	400	400	400
Control voltage	24	24	24	24	24
Safety Fuse (A)	25 (träge)	25 (träge)	63 (träge)	63 (träge)	63 (träge)
Dimensions (mm)					
Width	1071	1071	1352	1352	1380 / 2230
Depth	897	897	1145	1145	1272
Height	1083	1083	1200	1200	1531
Weight (kg)	380	395	1030 / 1080	1200 / 1250	1900 / 1965
Options	-	-	DMK 80 C2AW mechanical release unit	DMK 80 V2AW mechanical release unit	mechanical release unit