



## Hydraulic Filling Machine DF 250 X

### Professional Technical Features in a Compact Method of Construction

On account of its compact, robust, and highly efficient method of construction, the hydraulic filling machine DF 250 X is an ideal device for medium sized butcher's shops, for home-slaughtering and self-marketing.

Even so the DF 250 X is a mobile machine, its high dead-weight guarantees a good stability. Both the removable knee pedal and filling piston as well as the removable machine cover ensure a simple cleaning.

The high method of construction offers a perfect level to work on the machine and it allows the user to stand conveniently while working. The ergonomic knee lever is extremely easy to operate. Mounting the attached filling pipes by bolting with stainless-steel screws turns out to be very basic.

The closed oil system and its stainless-steel oil tank prevent detergent and condensation water from interrupting the oil circulation. This way, maintenance is needed to a low degree and the service life of both the hydraulic pump and the valves is increased. Since the piston rod is made of stainless-steel, a high service life of the hydraulic cylinders is guaranteed as well.



# Hydraulic Filling Machine DF 250 X



## Machine Type

- completely stainless-steel
- stainless-steel cylinders
- pistons simply removable
- infinitely variable filling speed
- removable knee pedal
- mobile edition
- 3 stainless-steel filling pipes
- removable machine cover

## Drive

- maintenance-free electric engine with hydraulic pump
- protective caps for push buttons
- 0,74 kW, 400 V, 50 Hz

## Hydraulics

- closed hydraulic system
- stainless-steel oil tank separately integrated in cabinet
- high hydraulic pump pressure

## Specifications

	DF 150 E	DF 250 X	DF 25 C	DF 40 X
Cylinder volume (litres)	15	25	25	40
Power (kW)	0,37	0,74	1,5	1,5
Pump pressure (bar)	120	130	150	150
Voltage	400	400	400	400
Control voltage	24	24	24	24
Safety Fuse (A)	16	16	16	16
Dimensions (mm)				
Height	1100	1170	1200	1115
Width	440	520	500	560
Depth	500	430	540	532
Weight (kg)	75	125	130	210
Accessories	Tool to dismantle pistons 3 filling pipes (14, 20, 30 mm)	Tool to dismantle pistons 3 filling pipes (14, 20, 30 mm)	Tool to dismantle pistons 3 filling pipes (14, 20, 30 mm)	Tool to dismantle pistons 3 filling pipes (14, 20, 30 mm)

## DMS Maschinensysteme

Lebensmittelmaschinen GmbH & Co KG  
An den Ziegelhütten 6 - 8  
D - 66127 Saarbrücken - Germany

Tel.: +49 (0)68 98 / 93 37 - 0  
Fax: +49 (0)68 98 / 93 37 - 29  
E-Mail: info@dms-maschinen.de  
Internet: www.dms-maschinen.de