



## Automatic Filling Machine DF 32 A

### The allrounder for the sausage kitchen


On account of its compact, robust and highly efficient method of construction, the automatic filling machine DF 32 A is an ideal device for filling, portioning and twisting of all kinds of sausages. With a portioning speed of up to 200 portions/minute and a portioning range of 5g to 10.000g (adjustable in 0,1g steps) the machine is ideal for medium sized butcher's shops, and for shift working supermarkets.

Even so the DF 32 A is a mobile machine, its high dead-weight guarantees a good stability. The user-friendly touchscreen allows to easily make all the adjustments in weight, number of portions, number of twists and the time between the portions.

The closed oil system and its stainless-steel oil tank prevent detergent and condensation water from interrupting the oil circulation. This way, maintenance is needed to a low degree and the service life of both the hydraulic pump and the valves is increased. Since the piston rod is made of stainless-steel, a high service life of the hydraulic cylinders is guaranteed as well.



# Automatic Filling Machine DF 32 A



## Machine type

- Completely stainless-steel
- Cylinder volume: 32 Ltrs.
- Stainless-steel cylinder
- Polyethylene piston
- Machine for filling, portioning, twisting of kinds of sausages
- Portioning speeds: up to 200 portions/minute
- Portioning range: 5g – 10.000g, adjustable in 0,1g steps
- Programmable are:
  - Weight of the portions
  - Number of portions
- Number of twists
- Time between portions
- User-friendly touchscreen
- Protection cover for touchscreen
- Mobile edition

## Drive

- Maintenance-free electric engine with hydraulic pump
- 2,6 kW / 400 V / 50 Hz
- CEE jack 16 A

## Hydraulics

- Closed hydraulic system
- Stainless-steel oil tank, separately integrated in cabinet
- Pump pressure: 130 bar

## Specifications

	DF 32 A
Cylinder volume (l)	32
Power (kW)	2,6
Pump pressure (bar)	160
Max portions/minute	200
No. of twists	0 - 10
Voltage (V)	400
Control voltage (V)	24
Safety fuse (A)	16 (delay)
Dimensions (mm)	
Width	700
Depth	745
Height	1570
Weight (kg)	380
Accessories	<ul style="list-style-type: none"> <li>▪ Tool to dismantle pistons</li> <li>▪ 3 filling pipes</li> <li>▪ (14, 20, 30 mm)</li> </ul>

## DMS Maschinensysteme

Lebensmittelmaschinen GmbH & Co KG  
An den Ziegelhütten 6 - 8  
D - 66127 Saarbrücken - Germany

Tel.: +49 (0)68 98 / 93 37 - 0  
Fax: +49 (0)68 98 / 93 37 - 29  
E-Mail: info@dms-maschinen.de  
Internet: www.dms-maschinen.de